



MATERIAL SAFETY DATA SHEET NPCA 1-84  
FOR COATINGS, RESINS, AND RELATED MATERIALS  
REPLACES NPCA 1-82

**MANUFACTURER'S NAME**

McCormick Paints  
2355 Lewis Avenue  
Rockville, MD 20851

**EMERGENCY TELEPHONE NO.**

CHEMTREC  
1-800-424-9300

**DATE OF PREPARATION:** June 1, 2007

**REVISED:** November 6, 2008

**INFORMATION TELEPHONE NO.**

1-301-770-3235

**SECTION I – PRODUCT IDENTIFICATION**

**PRODUCT NUMBER:** 45000 (45 Series)  
**PRODUCT NAME:** Interlok Semi-Gloss Interior/Exterior Acrylic Urethane DTM  
**PRODUCT CLASS:** Latex Paint

**SECTION II – HAZARDOUS INGREDIENTS**

INGREDIENT	PERCENT	OCCUPATIONAL EXPOSURE LIMIT		VAPOR PRESSURE	CAS NUMBER
		TLV-TWA	TLV-PEL		
n-Methyl-2Pyrrodidinone	1-1.2%	N/A	N/A	N/A	872504
Dipropylene glycol n-butyl ether	<2.0%	N/A	N/A	N/A	29911-28-2
NN-Diethylethanamine	<0.1%	1ppm	3ppm	N/A	121-44-8

Chronic Exposure: 1-Methyl-2-Pyrrodidinone has been shown to cause reproductive and developmental effects at very high maternally toxic doses, in experimental animals. These observations are not thought to be relevant to occupational use.

**SECTION III – PHYSICAL DATA**

**BOILING RANGE:** 212° F **VAPOR DENSITY:** X HEAVIER    LIGHTER THAN AIR  
**EVAPORATION RATE:**    FASTER X SLOWER THAN ETHER  
**% VOLATILE VOLUME:** 60 - 60.5 **WEIGHT/GALLON:** 10.6 Pounds  
**THEORETICAL VOC/VOS LESS THAN:** 150 Gms/L, 1.3 lbs/gal

**SECTION IV – FIRE AND EXPLOSION HAZARD DATA**

**FLAMMABILITY CLASS:** OSHA N/A DOT N/A  
FLASH POINT N/A LEL N/A

**EXTINGUISHING MEDIA:**    FOAM    "ALCOHOL" FOAM    CO2  
   DRY CHEMICAL X WATER FOG    OTHER

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None **SPECIAL FIREFIGHTING PROCEDURES:** None

**SECTION V – HEALTH HAZARD DATA**

**EFFECTS OF OVEREXPOSURE:**

**Inhalation:** Vapors or spray mists may be irritating to the eye, nose, throat and mucous membranes of the respiratory tract producing symptoms of headache and/or nausea in poorly ventilated areas.

**PHYSICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:**

**Skin Contact:** Prolonged or repeated contact with coating may cause skin irritation.  
**Eye Contact:** Direct eye contact will cause eye irritation.

---

**SECTION V – HEALTH HAZARD DATA (CONTINUED)**

---

**PRIMARY ROUTE(S) OF ENTRY:**  DERMAL  INHALATION  INGESTION

**EMERGENCY AND FIRST AID PROCEDURES:**

**Skin Contact:** Wash thoroughly with soap and water.

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes; consult a physician.

**Ingestion:** If victim is conscious, give 2 glasses of water and call a physician.

---

**SECTION VI – REACTIVITY DATA**

---

**STABILITY:**  UNSTABLE  STABLE

**HAZARDOUS POLYMERIZATION:**  MAY OCCUR  WILL NOT OCCUR

**HAZARDOUS DECOMPOSITION PRODUCTS:** Acetic acid, CO and CO<sub>2</sub>.

**CONDITIONS TO AVOID:** Freezing or temperature over 140° F.

**INCOMPATIBILITY (MATERIALS TO AVOID):** Any material that reacts violently with water.

---

**SECTION VII – SPILL OR LEAK PROCEDURES**

---

**STEPS TO BE TAKEN IN CASE MATERIALS ARE RELEASED OR SPILLED:**

Contain spill and remove with inert material (sand, earth, absorbent). Keep spill out of sewers and open bodies of water. Keep unnecessary people away, as floor may be slippery.

**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations.

---

**SECTION VIII – SAFE HANDLING AND USE INFORMATION**

---

**RESPIRATORY PROTECTION:** None required if good ventilation is maintained except if product is sprayed, then use mask (NIOSH approved). If TLV is exceeded then use canister or air hose mask.

**VENTILATION:** Mechanical-local exhaust at point of contaminant release (vapor, mist or dust).

**PROTECTIVE GLOVES:** Impervious required for repeated or prolonged contact.

**EYE PROTECTION:** Safety glasses (ANSI Z87.1.1979).

**OTHER PROTECTIVE EQUIPMENT:** Eyewash facility, emergency shower.

**HYGIENIC PRACTICES:** Wash hands before eating or using bathroom.

---

**SECTION X – SPECIAL PRECAUTIONS**

---

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:**

Store above 34° F and below 140° F.

**OTHER PRECAUTIONS:** Do not take internally.

This coating contains materials classified as nuisance particulates, for example Titanium dioxide, Calcium carbonate, etc. (See ACGIH TLV list, preface and appendix D), which may present at hazardous levels only during spraying this coating or sanding or abrading of the dried film.