



Commitment to Quality

**INTERIOR / EXTERIOR
ACRYLIC LATEX CAULK
with SILICONE**

PRODUCT DATA

GENERIC TYPE: Acrylic

DESCRIPTION: An all purpose, interior/exterior acrylic caulk manufactured to the highest quality specifications. Silicone formulation adds extra adhesion and low temperature flexibility. Provides a water resistant seal against air and moisture. Formulated to last up to 40 years. This product is paintable with latex or oil-based paints and mildew resistant. It is non flammable, contains a mild odor and can be cleaned up with soap and water. Meets ASTM Specifications C-834.

Features:

- Siliconized for Extra Adhesion
- All-Acrylic Polymer Base
- 40 Year Durability Guarantee
- Water-Based Formula
- Paintable
- Mildew Resistant
- Air/Moisture Resistant
- Available in White, Cool Platinum

RECOMMENDED USES: For caulking and sealing windows, base boards, door frames, moldings, siding and trim, corner joints, pipes, vents/ducts, chimney flashing, masonry, ceiling and wall joints. Adheres to wood, metal, brick, plaster, vinyl, drywall, aluminum, cement/concrete, painted surfaces and ceramics.

BENEFITS:

- Paintable with latex or oil-based paints.
- Protected against mildew discoloration.
- Stays flexible, eliminating cracking even at temperatures below freezing.
- Excellent exterior durability.
- Easy tooling, soap and water clean-up.
- Seals out air and moisture.
- Weather resistant.

Limited 40 Year Warranty: If this product cracks, peels or separates, when used as directed, WITHIN 40 YEARS after application, McCormick will replace this cartridge without charge upon presentation of proof of purchase and used cartridge. This limited warranty applies to residential non commercial use only. NO OTHER WARRANTIES ARE MADE, EXPRESSED, OR IMPLIED. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED IN DURATION TO THE DURATION OF THIS WARRANTY. McCormick Paints' liability under any warranty, whether expressed or implied, is LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT AND DOES NOT INCLUDE LABOR OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow limitations on how long an implied warranty lasts or exclusions or limitation of incidental damages, so the above limitation or exclusions may not apply to you. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

Rev Date 10/06

PHYSICAL CHARACTERISTICS

Surface Preparation: Remove old caulk. Clean all surfaces thoroughly to remove dirt, grease, wax, loose paint, dust, and oil. Remove mildew with bleach and detergent that does not contain ammonia.

Application Conditions: Apply at temperatures above 40°F but below 100°F. Do not apply when rain or freezing temperatures are expected within 24 hours.

Joint Size: Joints should not exceed 1/2" x 1/2" (9.5 mm x 9.5 mm). If depth of joints exceeds 1/2", use a suitable backing material. Not recommended for siding butt joints.

Smoothing/Clean-Up: Smooth with a wet finger or putty knife. Wipe off excess with damp cloth. Clean-up with soap and water before caulk dries (15 minutes).

Painting: Paintable with latex or oil-based paints in 2 hours depending on temperature and humidity. For best results, allow 24 hours for thorough drying.

Tack Free Time: Tack free in 30 minutes. Tooling time 10 minutes.

Flexibility: Good; will recover when compressed.

Mildew Resistance: Excellent. Cured caulk is mold and mildew resistant.

Water Resistance: Good. Intermittent water contact does not weaken the waterproof seal, but caulk should not be subjected to continuous long-term immersion.

Odor: Very mild odor.

Shrinkage: Seams cure with a slight curve.

Storage/Shelf Life: 1 year when stored properly. Best stored at temperatures between 40°F and 100°F.

Freeze/Thaw Stability: Minimum of five cycles at 0°F.

Packaging: 10 fl oz (296ml) Plastic Cartridge.

CAUTIONS: **KEEP OUT OF THE REACH OF CHILDREN.
DO NOT TAKE INTERNALLY.
KEEP FROM FREEZING.**

MANUFACTURED BY:



Commitment to Quality

2355 Lewis Avenue, Rockville, MD 20851

Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814

www.mccormickpaints.com

K-10