



**INTERIOR PENETRATING
WOOD STAIN
9101194 – GUNSTOCK COLOR**

PRODUCT DATA

Generic Type: Soya Alkyd Resin

DESCRIPTION: McCormick Interior Penetrating Wood Stain is a premium quality, alkyd based; penetrating interior wood stain formulated to penetrate new or thoroughly sanded uncoated wood surfaces. Its depth and clarity of tone emphasizes the natural pattern and characteristics of the wood grain.

Features:

- Resistant to Peeling
- Attractive Finish
- Enhances Wood Grain
- Easy Application

RECOMMENDED USES: For use on interior uncoated wood surfaces such as furniture, paneling, doors, cabinets, and trim. May be top-coated with conventional interior alkyd/oil polyurethane modified clear finishes.

NOT RECOMMENDED: DO NOT USE UNDER AROMATIC SOLVENT-BASED CLEAR FINISHES AND WATER-BASED POLYURETHANES.

CAUTION:

APPLY A TEST SAMPLE AND INSPECT FOR CORRECT COLOR **BEFORE** APPLYING STAIN. FURTHER APPLICATION CONSTITUTES ACCEPTANCE OF COLOR.

McCormick Paints assumes no responsibility, expressed or implied, for an unsatisfactory color after it has been applied.

PHYSICAL CHARACTERISTICS

Colors: Clear

Vehicle Type: Soya Alkyd Resin

VOC/VOS: Less than 635 g/L; 4.6 lb. /gal

Volume Solids (Avg.): 25% ± 2%

Weight Solids (Avg.): 32% ± 2%

Viscosity: 10-15 seconds (#4 Ford Cap)

Suggested Film Thickness:

Wet: N/A

Dry: N/A

Theoretical Coverage per Gallon:

500 sq ft

Gloss Level: N/A

Sheen: N/A

Drying Time @77°F & 50% R.H.:

To Touch: 4 hours

Recoat: 16 hours. Allow additional drying time during humid or cooler weather.

Min. Surface/Air Temperature at Application: 50°F

Max. Surface/Air Temperature at Application: 110°F

Flash Point: 105°F

Heat Resistance: 150°F Intermittent

Application: Brush or Cloth

Thinning:

Brush and Roller: Not Recommended

Clean Up: Mineral Spirits

Packaging: Quart

Weight per Gallon: 6.3 – 6.5 lb. /gal

GREEN WISE®	LEED	SCAQMD	OTC
NO	NO	NO	YES

INTERIOR PENETRATING WOOD STAIN - GUNSTOCK
9101194

SURFACE PREPARATION

All wood surfaces must be clean and dry before staining. Remove grease or oils with appropriate cleaners. Remove any previous finish completely and sand thoroughly. Uncoated open grained wood such as oak or walnut should be filled with paste wood filler. Do not fill closed-grained woods such as maple, birch, or pine.

APPLICATION

Stir well before use and stir periodically while using this product to assure color uniformity. This product may be applied by brush or cloth. Allow to dry 5-10 minutes, and then wipe off excess with a clean lint free cloth. The color obtained will depend on the color and porosity of the wood being stained, how long it is allowed to dry before wiping and how hard it is wiped. If a second coat is desired allow 16 hours before recoating and repeat in the same manner. It is recommend to test the wood stain on small pieces of wood from the job site and allow to dry thoroughly to assure the correct color is being applied. Do not apply when temperature is below 45°F.

CAUTIONS --- Lead Hazard: WARNING!

If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

USE ONLY WITH ADEQUATE VENTILATION. Wear appropriate respiratory protection when sanding or spraying this product. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid contact with eyes and skin.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CONTAINER LABELING COMPLIES WITH APPLICABLE STATE RIGHT-TO-KNOW ACTS. For additional safety and health information, please refer to the Safety Data Sheet (SDS).

Rev 02/18

MANUFACTURED BY:

McCormick Paints
THE PAINT THE PROS USE

2355 Lewis Avenue, Rockville, MD 20851
Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814
www.mccormickpaints.com

PRODUCT DATA SHEET