



DRY FALL
INTERIOR WATERBORNE ACRYLIC
01219 White – Flat Sheen

PRODUCT DATA

GENERIC TYPE: Acrylic

DESCRIPTION: McCormick Interior Waterborne Acrylic Dry Fall is a water-based coating designed for spray application to interior ceilings, walls, and structural steel. The coating overspray will fall dry within 10 feet of the surface before settling on floors or equipment and can easily be swept or wiped up for easy clean up of work areas. Water-based characteristics contribute to a safer and reduced hazard application because of its low odor and low solvent formulation.

Note: low temperatures, or high humidity, and/or excess colorant level may affect dry fall characteristics of this product, and increase the distance required to achieve an acceptable dry fall of this product.

Features:

- Reduces Clean Up Costs
- Requires Minimal Surface Preparation
- High Light Reflectance
- Low Odor

RECOMMENDED USES: For use on interior ceilings, walls, and structural steel in warehouses, industrial, commercial, and institutional buildings.

COMPATIBLE COATINGS: May be applied over properly prepared latex or alkyd/oil finishes. See application instructions for proper substrate primer.

Primers:

- McCormick 1st Step Underlok Interior/Exterior Acrylic Latex Multi-Purpose Primer 06452
- McCormick 1st Step Interior/Exterior White Metal Rust Inhibitive Alkyd Primer 06453
- McCormick Unix Interior/Exterior Stain Blocking and Multi-Purpose Primer 06460

PHYSICAL CHARACTERISTICS

Colors: 01219 White

Vehicle Type: Acrylic

VOC/VOS: Less than 100 g/L; 0.8 lb. /gal

Volume Solids (Avg.): 36.3% ± 2%

Weight Solids (Avg.): 54.4% ± 2%

Viscosity: 100-105 KU

Suggested Film Thickness:

Spray Only: 6.0 mils wet, 2.1 mils dry

Coverage: 180-275 sq. /gal approximate

Theoretical Coverage per Gallon:

464 sq. ft. /gal @ 1 mil dry

Gloss Level: 5-10 units @60°

Sheen: 5-10 units @ 85°

Drying Time @ 77°F & 50% R.H.:

To Touch: 30 minutes

Recoat: 2 hours. Allow additional drying time during humid or cooler weather.

Min. Surface/Air Temperature at Application: 50°F

Max. Surface/Air Temperature at Application: 110°F

Flash Point: Non Flammable

Heat Resistance: 130°F

Application: Spray

Thinning: Not Recommended

Clean Up: Warm Water and Detergent

Packaging: Five Gallon

Weight per Gallon: 11.3 - 11.6 lb. /gal

This product is currently certified under MPI #118

GREEN WISE®	LEED	SCAQMD	OTC
NO	YES	YES	YES

INTERIOR WATERBORN ACRYLIC DRY FALL
01219 White

APPLICATION INSTRUCTIONS

For the following surfaces, prime as indicated and finish with 1 coat of McCormick Interior Waterborne Acrylic Dry 01219 White.

SURFACE PREPARATION

Previously Painted Surfaces: All surfaces must be internally dry, thoroughly clean, and free from dirt, grease, kalsomine, wallpaper adhesive, loose and peeling paint, and other surface contaminants that might impair adhesion. Remove loose and peeling paint and sand edges smooth. Spackle nail holes and cracks; sand and touch-up before finishing. Dull glossy areas by sanding and prime with McCormick Underlok Interior/Exterior Acrylic Latex Multi-Purpose Primer 06452. Any exposed substrate should be spot primed with the appropriate McCormick primer for unpainted surfaces listed below.

Unpainted Drywall: Spackle nail holes and cracks; sand smooth and wipe clean. Self prime or prime with McCormick 1st Step Interior Latex Enamel Undercoater and Primer Sealer 06441.

Unpainted Galvanized Metal: Clean factory surface treatment by wiping surface with clean rags wet with mineral spirits. Old galvanized metal surfaces should be lightly sanded, wiped clean and self primed with McCormick Interior Waterborne Acrylic Dry Fall Semi-Gloss 01219 or with McCormick Underlok Interior/Exterior Acrylic Latex Multi-Purpose Primer 06452.

Unpainted Ferrous Metal: Prime with McCormick 1st Step Interior/Exterior White Metal Rust Inhibitive Alkyd Primer 06453.

APPLICATION

Always stir well before use. Additives for ease of application or to promote adhesion are not recommended. Do not apply if material, substrate, or ambient temperature is below 50°F or above 110°F. Apply by spray application, thin with clean water, up to one pint per gallon if necessary.

Application Equipment:

- Apply by spray only.
- Manufacturers listed below are a guide. Others may be used. Changes in pressure and tip size may be required to achieve proper application.

Airless Spray:

Pump: Graco / Titan

High Pressure Filter: 60 Mesh

Fluid Hose: ¼" x 50'

Minimum pressure to avoid fingering: 2000 psi

CAUTIONS --- Lead Hazard: WARNING!

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Contains Crystalline Silica in an Encapsulated State:

If the dry paint film is sanded, the dust emitted can contain crystalline silica which has been shown to cause cancer under long term exposure. **USE ONLY WITH ADEQUATE VENTILATION.** Wear appropriate respiratory protection when sanding or spraying this product. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid contact with eyes and skin.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CONTAINER LABELING COMPLIES WITH APPLICABLE STATE RIGHT-TO-KNOW ACTS. For additional safety and health information, please refer to the Safety Data Sheet (SDS)

Rev Date 11/16

MANUFACTURED BY:

McCormick Paints
THE PAINT THE PROS USE

2355 Lewis Avenue, Rockville, MD 20851

Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814

www.mccormickpaints.com

PRODUCT DATA SHEET