



PERMALOK
INTERIOR / EXTERIOR
100% ACRYLIC TEXTURE COATING
01261

PRODUCT DATA

GENERIC TYPE: Acrylic Latex

DESCRIPTION: McCormick Permalok Interior/Exterior 100% Acrylic Texture Coating is a high performance decorative high build, water resistant acrylic emulsion used to protect above grade vertical masonry surfaces. This heavy aggregate filled coating provides an attractive breathable protective coating that helps hide defects while enhancing the appearance of masonry surfaces. McCormick Acrytex Interior / Exterior 100% Acrylic Texture Coating passes wind driven rain specification, TT-C-555B and ASTM D6904-3

RECOMMENDED USES: Ideal for use on brick, concrete block (CMU), masonry, fiber cement, stucco, and EFIS. May be used on incidental primed wood and metal. Recommended for use on tilt-up buildings, hotels, resorts, condominiums, hospitals, schools, concrete parking garage overheads, and residential homes.

Features:

- Breathable
- Excellent Stain Resistance
- Excellent Color Retention
- Superior Adhesion
- Resists Damage from Freeze-Thaw Cycles
- UV Resistance

Benefits:

- Protects substrate over a wide temperature range
- One Coat Application
- Long Term Protection

Physical Properties:

- Wind Driven Rain.....Passes ASTM D6904-3
- Water Vapor Permanence..... ASTM D1653
- 9.0 perms
- Mildew Resistance.....ASTM D3273/74

PHYSICAL CHARACTERISTICS

- Colors:** White, Special Order Colors
- Vehicle Type:** Acrylic Latex
- VOC/VOS:** Less than 50 g/L, 0.4 lb. /gal
- Volume Solids (Avg.):** 42% ± 2%
- Weight Solids (Avg.):** 56% ± 2%
- Viscosity:** 120 KU
- Theoretical Coverage per Gallon:**
 - Brush and Roll:** Small areas only
 - Spray:** 80-100 sq ft per gallon
- Gloss Level:** N/A
- Drying Time @ 77°F and 50% R.H.:**
 - To Touch:** 4 hours
 - Recoat:** 24 hours. Allow additional drying time during humid or cooler weather.
- Min. Surface/Air Temperature at Application:** 50°F (10°C)
- Max. Surface/Air Temperature at Application:** 110°F (38°C)
- Sheen:** N/A
- Flash Point:** N/A
- Heat Resistance:** 150°F
- Application:** Spray Only
- Thinning:** Not Recommended
 - Spray:** Texture Applicator
- Clean Up:** Warm Water and Detergent. Flush equipment with compliant solvent to prevent rusting of equipment.
- Packaging:** 5 Gallon, 55 Gallon
- Weight per Gallon:** 10.6-10.8 lb. /gal

NOT RECOMMENDED: Do not use on floors, decks, steps, or other underfoot areas. This product is not intended for immersion service or situations characterized by high heat or presence of corrosive chemicals.

This Product is currently certified under MPI #42

GREEN WISE®	LEED	SCAQMD	OTC
NO	YES	YES	YES

APPLICATION INSTRUCTIONS

For the following surfaces, prime as indicated and finish with 1 coat of McCormick Permalok Interior/Exterior 100% Acrylic Texture Coating 01261.

SURFACE PREPARATION

Patching and Sealing: All voids and cracks should be patched with either an elastomeric patching compound or McCormick Flexseal Elastomeric Sealant, whichever is most appropriate. All expansion and control joints, etc should be sealed with McCormick Flexseal Elastomeric Sealant. Cracked mortar joints should be replaced and "tuck-pointed" with new mortar.

Previously Painted Surfaces: All surfaces must be internally dry, thoroughly clean, and free from dirt, grease, excessive chalk, efflorescence, form release agents, loose paints, and other foreign matter. Remove mildew by scrubbing with an EPA registered solution to kill mildew or mold bacteria. Rinse with clean water and allow to dry thoroughly before applying top coat.

Unpainted Masonry: Allow new masonry to cure 30 days before painting. Allow additional curing time during humid or cooler weather. New masonry should have a PH of 13 or less. If painting cannot wait 30 days, allow surface to dry for a minimum of 7 days and prime with McCormick Permalok Interior/Exterior Acrylic Masonry Surface Conditioner 01322 or McCormick Permalok Interior / Exterior 100% Acrylic Masonry Primer 06451, depending on type of masonry.

Wood: McCormick State House Exterior Acrylic Latex Primer 06438.

Galvanized & Aluminum Metals: McCormick State House Exterior Acrylic Latex Primer 06458.

Ferrous Metal: McCormick 1st Step White Metal Rust Inhibitive Primer 06445.

APPLICATION

This product is ready to use. Mechanically stir material at a low speed to ensure uniformity prior to application. Do not thin. Do not apply if surface/air temperature is below 50°F (32°C) or above 110°F (38°C). Apply by professional hopper gun texture sprayer. Use brush and roller on small areas only.

APPLICATION EQUIPMENT

Graco RTX5000PX Texture Sprayer or for large projects Graco HTX2030 Texture Sprayer.

CAUTIONS --- Lead Hazard: WARNING!

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

USE ONLY WITH ADEQUATE VENTILATION. Wear appropriate respiratory protection when sanding or spraying this product. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid contact with eyes and skin.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CONTAINER LABELING COMPLIES WITH APPLICABLE STATE RIGHT-TO-KNOW ACTS. For additional safety and health information, please refer to the Safety Data Sheet (SDS).

Rev 03/17

MANUFACTURED BY:

McCormick Paints
THE PAINT THE PROS USE

2355 Lewis Avenue, Rockville, MD 20851

Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814

www.mccormickpaints.com

PRODUCT DATA SHEET