



**INTERIOR PENETRATING  
WOOD STAIN  
9101244 – BUTTERSCOTCH COLOR**

**PRODUCT DATA**

**Generic Type:** Soya Alkyd Resin

**DESCRIPTION:** McCormick Interior Penetrating Wood Stain is a premium quality, alkyd based; penetrating interior wood stain formulated to penetrate new or thoroughly sanded uncoated wood surfaces. Its depth and clarity of tone emphasizes the natural pattern and characteristics of the wood grain.

**Features:**

- Resistant to Peeling
- Attractive Finish
- Enhances Wood Grain
- Easy Application

**RECOMMENDED USES:** For use on interior uncoated wood surfaces such as furniture, paneling, doors, cabinets, and trim. May be top-coated with conventional interior alkyd/oil polyurethane modified clear finishes.

**NOT RECOMMENDED:** DO NOT USE UNDER AROMATIC SOLVENT-BASED CLEAR FINISHES AND WATER-BASED POLYURETHANES.

**CAUTION:**

APPLY A TEST SAMPLE AND INSPECT FOR CORRECT COLOR **BEFORE** APPLYING STAIN. FURTHER APPLICATION CONSTITUTES ACCEPTANCE OF COLOR.

McCormick Paints assumes no responsibility, expressed or implied, for an unsatisfactory color after it has been applied.

**PHYSICAL CHARACTERISTICS**

**Colors:** Clear

**Vehicle Type:** Soya Alkyd Resin

**VOC/VOS:** Less than 635 g/L; 4.6 lb. /gal

**Volume Solids (Avg.):** 25% ± 2%

**Weight Solids (Avg.):** 32% ± 2%

**Viscosity:** 10-15 seconds (#4 Ford Cap)

**Suggested Film Thickness:**

**Wet:** N/A

**Dry:** N/A

**Theoretical Coverage per Gallon:**

500 sq ft

**Gloss Level:** N/A

**Sheen:** N/A

**Drying Time @77°F & 50% R.H.:**

**To Touch:** 4 hours

**Recoat:** 16 hours. Allow additional drying time during humid or cooler weather.

**Min. Surface/Air Temperature at Application:** 50°F

**Max. Surface/Air Temperature at Application:** 110°F

**Flash Point:** 105°F

**Heat Resistance:** 150°F Intermittent

**Application:** Brush or Cloth

**Thinning:**

**Brush and Roller:** Not Recommended

**Clean Up:** Mineral Spirits

**Packaging:** Quart

**Weight per Gallon:** 6.3 – 6.5 lb. /gal

GREEN WISE®	LEED	SCAQMD	OTC
NO	NO	NO	YES

**INTERIOR PENETRATING WOOD STAIN - GUNSTOCK  
9101244**

---

**SURFACE PREPARATION**

All wood surfaces must be clean and dry before staining. Remove grease or oils with appropriate cleaners. Remove any previous finish completely and sand thoroughly. Uncoated open grained wood such as oak or walnut should be filled with paste wood filler. Do not fill closed-grained woods such as maple, birch, or pine.

**APPLICATION**

Stir well before use and stir periodically while using this product to assure color uniformity. This product may be applied by brush or cloth. Allow to dry 5-10 minutes, and then wipe off excess with a clean lint free cloth. The color obtained will depend on the color and porosity of the wood being stained, how long it is allowed to dry before wiping and how hard it is wiped. If a second coat is desired allow 16 hours before recoating and repeat in the same manner. It is recommend to test the wood stain on small pieces of wood from the job site and allow to dry thoroughly to assure the correct color is being applied. Do not apply when temperature is below 45°F.

**CAUTIONS --- Lead Hazard: WARNING!**

If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**USE ONLY WITH ADEQUATE VENTILATION.** Wear appropriate respiratory protection when sanding or spraying this product. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid contact with eyes and skin.

**First Aid:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CONTAINER LABELING COMPLIES WITH APPLICABLE STATE RIGHT-TO-KNOW ACTS.** For additional safety and health information, please refer to the Safety Data Sheet (SDS).

Rev 02/18

MANUFACTURED BY:

**McCormick Paints**  
THE PAINT THE PROS USE

2355 Lewis Avenue, Rockville, MD 20851  
Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814  
[www.mccormickpaints.com](http://www.mccormickpaints.com)

**PRODUCT DATA SHEET**