



CEILING WHITE
INTERIOR FLAT VINYL ACRYLIC
01040

PRODUCT DATA

GENERIC TYPE: Vinyl Acrylic

DESCRIPTION: McCormick Interior Flat Vinyl Acrylic Ceiling White is a premium quality interior white that is designed for painting ceilings where a uniform flat finish is desired. Helps hide surface imperfections.

Features:

- Good Hiding
- Excellent Light Reflectance
- Spatter Resistant
- Low Odor

RECOMMENDED USES: For use on properly prepared drywall, cured plaster (30 days), and acoustical ceiling tile. When applied over acoustical ceiling tile acoustic properties will not be destroyed; therefore, the surface remains sound absorbent.

COMPATIBLE COATINGS: May be applied over properly prepared latex or alkyd/oil finishes. See application instructions for proper substrate primer.

Primers:

- McCormick 1st Step Zero VOC Interior Vinyl Primer Sealer 06431
- McCormick uniX Multi-Purpose and Stain Blocking Interior/Exterior Primer 06460

NOT RECOMMENDED: Do not paint over vinyl wallcoverings. Vinyl wallcoverings can lose adhesion through age or from new or previous paint applications. Do not use as a trim paint, higher sheen finishes are recommended for these areas.

PHYSICAL CHARACTERISTICS

Colors: Off White
Vehicle Type: Vinyl Acrylic
VOC/VOS: Less than 50 g/L, 0.4 lb. /gal
Volume Solids (Avg.): 32% ± 2%
Weight Solids (Avg.): 51% ± 2%
Viscosity: 90-95 KU
Suggested Film Thickness:
Brush and Roll: 4.0 mils wet, 1.6 mils dry
Spray: 6 mils wet, 2.4 mils dry
Theoretical Coverage per Gallon:
 400 sq ft @ 1.6 mils DFT
Gloss Level: N/A
Sheen: 0.9-1.1 units @ 85°
Drying Time @77°F & 50% R.H.:
To Touch: 30 minutes
Recoat: 4 hours. Allow additional drying time during humid or cooler weather.
Min. Surface/Air Temperature at Application:
 50°F
Max. Surface/Air Temperature at Application:
 110°F
Flash Point: N/A
Heat Resistance: 150°F Intermittent
Application: Brush, Roller, or Spray
Thinning:
Brush and Roller: Not Recommended
Spray: Up to One Pint of Water per Gallon
Clean Up: Warm Water and Detergent
Packaging: Gallon and Five Gallon
Weight per Gallon: 11.6 – 11.8 lb/gal



GREEN WISE®	LEED	SCAQMD	OTC
YES	YES	YES	YES

CEILING WHITE INTERIOR FLAT VINYL ACRYLIC 01040

APPLICATION INSTRUCTIONS

For the following surfaces, prime as indicated and finish with 2 coats of McCormick Ceiling White Interior Flat Vinyl Acrylic 01040.

SURFACE PREPARATION

Previously Painted Surfaces: All surfaces must be internally dry, thoroughly clean, and free from dirt, grease, kalsomine, wallpaper adhesive, loose and peeling paint, and other surface contaminants that might impair adhesion. Remove loose and peeling paint and sand edges smooth. Spackle nail holes and cracks; sand and touch-up before finishing. Dull glossy areas by sanding. Prime with McCormick Underlok Interior/Exterior Acrylic Latex Multi-Purpose Primer 06452. Any exposed substrate should be spot primed with appropriate McCormick primer for unpainted surfaces listed below.

Unpainted Drywall: Spackle nail holes and cracks; sand smooth and wipe clean. Self-prime or prime with McCormick 1st Step Zero VOC Interior Vinyl Primer Sealer 06431.

Unpainted Plaster: Allow new plaster to age 30 days. Prime with McCormick Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451.

APPLICATION

Always stir well before use. Additives for ease of application or to promote adhesion are not recommended. Do not apply if material, substrate, or ambient temperature is below 50°F or above 110°F. Relative humidity should be below 90%. Apply by brush, roller, or spray. For best roller application results use a 3/8" to 1/2" nap cover. For spray application, thin with clean water, up to one pint per gallon if necessary.

APPLICATION EQUIPMENT:

- Apply by brush, roller, or spray.
- Manufacturers listed below are a guide. Others may be used. Changes in pressure and tip size may be required to achieve proper application.

Airless Spray:

Pump: Graco / Titan

High Pressure Filter: 60 Mesh

Fluid Hose: 1/4" x 50'

Tips: 0.015" - 0.021"

Minimum pressure to avoid fingering: 2000 psi

CAUTIONS --- Lead Hazard: WARNING!

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

USE ONLY WITH ADEQUATE VENTILATION. Wear appropriate respiratory protection when sanding or spraying this product. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid contact with eyes and skin.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CONTAINER LABELING COMPLIES WITH APPLICABLE STATE RIGHT-TO-KNOW ACTS. For additional safety and health information, please refer to the Safety Data Sheet (SDS).

Rev 11/22

MANUFACTURED BY:

McCormick Paints
THE PAINT THE PROS USE

11200 Rockville Pike, Suite 504 Rockville, MD 20852
Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814
www.mccormickpaints.com

PRODUCT DATA SHEET