



# PREMIUM WHITE

## INTERIOR HIGH-BUILD SEMI-GLOSS ACRYLIC ENAMEL 01245

### PRODUCT DATA

**GENERIC TYPE:** Acrylic Latex

**DESCRIPTION:** A premium quality interior wall and trim paint specifically formulated to hide in one coat.

**Features:**

- One Coat Hiding
- Excellent Washability
- Exceptional Flow & Leveling
- Non-Yellowing
- Soil Resistant

**RECOMMENDED USES:** For use on properly prepared interior drywall, cured plaster (30 days), wood, metal, and aged masonry (60 days). Ideally suited for walls and ceilings in kitchens, baths and other frequently cleaned areas, such as architectural woodwork, doors, trim and cabinets. Its high hiding, quick drying, and excellent flow and leveling properties make Premium White High-Build Latex Semi-Gloss and excellent choice in all residential and commercial applications.

**COMPATIBLE COATINGS:** May be applied over properly prepared latex or alkyd/oil finishes. See application instructions for proper substrate primer.

**Primers:**

- McCormick Interior/Exterior Latex Block Filler 01015
- McCormick 1<sup>st</sup> Step Interior Latex Enamel Undercoater and Primer Sealer 06441
- McCormick uniX Multi-Purpose Stain Blocking Interior/Exterior Primer 06460
- McCormick Underlok Interior/Exterior Acrylic Latex Multi-Purpose Primer 06452
- McCormick Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451

### PHYSICAL CHARACTERISTICS

**Colors:** White

**Vehicle Type:** Acrylic Latex

**VOC/VOS:** Less than 100 g/L, 0.8 lb. /gal

**Volume Solids (Avg.):** 40.3% ± 2%

**Weight Solids (Avg.):** 56.2% ± 2%

**Viscosity:** 95 KU

**Suggested Film Thickness:**

**Brush and Roll:** 3 mils wet, 1.2 mils dry

**Spray:** 6 mils wet, 2.4 mils dry

**Theoretical Coverage per Gallon:**

400 sq ft @ 1.5 mils DFT

**Gloss Level:** 55-65 units @ 60°

**Sheen:** N/A

**Drying Time @ 77°F & 50% R.H.:**

**To Touch:** 2 hours

**Recoat:** 8 hours. Allow additional drying time during humid or cooler weather.

**Min. Surface/Air Temperature at Application:** 50°F

**Max. Surface/Air Temperature at Application:** 110°F

**Flash Point:** Non Flammable

**Heat Resistance:** 150°F Intermittent

**Application:** Brush, Roller, or Spray

**Thinning:**

**Brush and Roller:** Not Recommended

**Spray:** Up to One Pint of Water per Gallon

**Clean Up:** Warm Water and Detergent

**Packaging:** Quart, Gallon and Five Gallon

**Weight per Gallon:** 11.4 lb. /gal

**NOT RECOMMENDED:** Do not paint over wall coverings. Vinyl wallcoverings can lose adhesion through age or from new or previous paint applications.

GREEN WISE®	LEED	SCAQMD	OTC
NO	YES	NO	YES

**PREMIUM WHITE INTERIOR HIGH-BUILD SEMI-GLOSS ACRYLIC ENAMEL  
01245**

---

### APPLICATION INSTRUCTIONS

For the following surfaces, prime as indicated and finish with 2 coats of McCormick Premium White Interior High Build Semi-Gloss Acrylic Enamel 01245.

### SURFACE PREPARATION

**Previously Painted Surfaces:** All surfaces must be internally dry, thoroughly clean, and free from dirt, grease, kalsomine, wallpaper adhesive, loose and peeling paint, and other surface contaminants that might impair adhesion. Remove loose and peeling paint and sand edges smooth. Spackle nail holes and cracks; sand and touch-up before finishing. Dull glossy areas by sanding, prime with McCormick Underlok Interior/Exterior Acrylic Latex Multi-Purpose Primer 06452. Any exposed substrate should be spot primed with the appropriate McCormick primer for unpainted surfaces listed below.

**Unpainted Drywall:** Spackle nail holes and cracks; sand, smooth, and wipe clean. Self prime or prime with McCormick 1<sup>st</sup> Step Interior Latex Enamel Undercoater and Primer Sealer 06441.

**Unpainted Plaster:** Allow new plaster to age 30 days. Prime with McCormick Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451.

**Unpainted Masonry:** Allow new masonry to age 60 days.

**Brick and Smooth Concrete:** Prime with McCormick Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451. **Concrete Block:** Prime with McCormick Interior-Exterior Latex Block Filler 01015.

**Unpainted Wood:** Fill all nail holes and open joints with interior wood putty. Sand smooth and wipe clean. Prime with McCormick 1<sup>st</sup> Step Interior Latex Enamel Undercoater and Primer Sealer 06441.

**Unpainted Galvanized Metal:** Clean factory surface treatment by wiping surface with clean rags wet with mineral spirits. Old galvanized metal surfaces should be lightly sanded, wiped clean and primed with uniX Multi-Purpose Stain Blocking Interior/Exterior Primer 06460.

### APPLICATION

Always stir well before use. Additives for ease of application or to promote adhesion are not recommended. Do not apply if material, substrate, or ambient temperature is below 50°F or above 110°F. Relative humidity should be below 90%. Apply by brush, roller, or spray. For best brush application results, use a quality synthetic filament brush. For roller application, use a ½" to ¾" nap cover. For spray application, thin with clean water, up to one pint per gallon if necessary.

### WASHING INSTRUCTIONS

Allow 30 days after application before washing. Remove common dirt stains by using a soft cloth or sponge, warm water and mild detergent.

### APPLICATION EQUIPMENT

- Apply by brush, roller, or spray.
- Manufacturers listed below are a guide. Others may be used. Changes in pressure and tip size may be required to achieve proper application.

#### **Airless Spray:**

Pump: Graco / Titan

High Pressure Filter: 60 Mesh

Fluid Hose: ¼" x 50'

Tips: 0.015" - 0.021"

Minimum pressure to avoid fingering: 2000 psi

### CAUTIONS --- Lead Hazard: WARNING!

**If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**

**USE ONLY WITH ADEQUATE VENTILATION.** Wear appropriate respiratory protection when sanding or spraying this product. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid contact with eyes and skin.

**First Aid:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CONTAINER LABELING COMPLIES WITH APPLICABLE STATE RIGHT-TO-KNOW ACTS.** For additional safety and health information, please refer to the Safety Data Sheet (SDS).

Rev Date 07/19

MANUFACTURED BY:

**McCormick Paints**  
THE PAINT THE PROS USE

2355 Lewis Avenue, Rockville, MD 20851

Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814

[www.mccormickpaints.com](http://www.mccormickpaints.com)

**PRODUCT DATA SHEET**