



**RENEW**  
**----- XC -----**  
**INTERIOR LATEX FLAT**  
**26 SERIES**

**PRODUCT DATA**

**GENERIC TYPE:** Vinyl Latex

**DESCRIPTION:** RENEW<sup>XC</sup> Interior Latex Flat is a high hiding, professional wall and ceiling paint. It is a quick drying coating that applies easily by brush, roller, or spray application.

**Features:**

- GREEN WISE<sup>®</sup> certified
- Attractive Flat Finish
- Low Spatter
- Low Odor
- Water Clean Up

**RECOMMENDED USES:** For use on new construction, commercial buildings, renovation, and maintenance projects. An excellent finish for interior drywall, cured plaster (30 days), aged masonry (60 days), and properly prepared metal surfaces.

**COMPATIBLE COATINGS:** May be applied over properly prepared latex or alkyd/oil finishes. See application instructions for proper substrate primer.

**Primers:**

- McCormick Interior/Exterior Latex Block Filler 01015
- McCormick 1<sup>st</sup> Step Interior Latex Enamel Undercoater and Primer Sealer 06441
- McCormick uniX Multi-Purpose Stain Blocking interior/Exterior Primer 06460
- McCormick Underlok Interior Exterior Acrylic Latex Multi-Purpose Primer 06452
- McCormick Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451

**PHYSICAL CHARACTERISTICS**

**Colors:** White, Standard Colors  
**Vehicle Type:** Acrylic Latex  
**VOC/VOS:** Less than 50 g/L, 0.4 lb/gal  
**Volume Solids (Avg.):** 30.5% ± 2%  
**Weight Solids (Avg.):** 47.0% ± 2%  
**Viscosity:** 95-105 KU  
**Suggested Film Thickness:**  
     **Brush:** 4.0 mils wet, 1.0 mil dry  
     **Spray:** 6 mils wet, 1.8 mils dry  
**Theoretical Coverage per Gallon:**  
 400 sq ft @ 1.0 mil DFT  
**Gloss Level:** N/A  
**Sheen:** 0.9 - 1.3 units @ 85°  
**Drying Time @ 77°F & 50% R.H.:**  
     **To Touch:** 30 minutes  
     **Recoat:** 4 hours. Allow additional drying time during humid or cooler weather.  
**Min. Surface/Air Temperature at Application:**  
 50°F  
**Max. Surface/Air Temperature at Application:**  
 110°F  
**Flash Point:** Non-Flammable  
**Heat Resistance:** 150°F Intermittent  
**Application:** Brush, Roller, or Spray  
**Thinning:**  
     **Brush and Roller:** Not Recommended  
     **Spray:** Up to One Pint of Water per Gallon  
**Clean Up:** Warm Water and Detergent  
**Packaging:** Five Gallon  
**Weight per Gallon:** 10.5 - 10.8 lb/gal

**NOT RECOMMENDED:** Do not paint over wallcoverings. Vinyl wallcoverings can lose adhesion through age or from new or previous paint applications. Do not use as a trim paint, higher sheen finishes are recommended for these areas.



GREEN WISE <sup>®</sup>	LEED	SCAQMD	OTC
YES	YES	YES	YES

**RENEW<sup>XC</sup> INTERIOR LATEX FLAT  
26 SERIES**

**APPLICATION INSTRUCTIONS**

For the following surfaces, prime as indicated and finish with 2 coats of McCormick **RENEW<sup>XC</sup>** Interior Latex Flat 26 Series.

**SURFACE PREPARATION**

**Previously Painted Surfaces:** All surfaces must be internally dry, thoroughly clean, and free from dirt, grease, kalsomine, wallpaper adhesive, loose and peeling paint, and other surface contaminants that might impair adhesion. Remove loose and peeling paint and sand edges smooth. Spackle nail holes and cracks. Sand and touch-up before finishing. Dull glossy areas by sanding. Prime with McCormick Underlok Interior Exterior Acrylic Latex Multi-Purpose Primer 06452. Any exposed substrate should be spot primed with appropriate McCormick primer as for unpainted surfaces listed below.

**Unpainted Drywall:** Spackle nail holes and cracks. Sand smooth and wipe clean. Self prime or prime with McCormick 1<sup>st</sup> Step Interior Latex Enamel Undercoater and Primer Sealer 06441.

**Unpainted Plaster:** Allow new plaster to age 30 days. Prime with McCormick Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451.

**Unpainted Masonry:** Allow new masonry to age 60 days.

**Brick and Smooth Concrete:** Prime with McCormick Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451. **Concrete Block:** Prime with McCormick Interior-Exterior Latex Block Filler 01015.

**Unpainted Wood:** Fill all nail holes and open joints with interior wood putty. Sand smooth and wipe clean. Prime with McCormick 1<sup>st</sup> Step Interior Latex Enamel Undercoater and Primer Sealer 06441.

**Unpainted Galvanized Metal:** Clean new galvanized surface by wiping surface with clean rags wet with mineral spirits. Prime with McCormick uniX Multi-Purpose Stain Blocking interior/Exterior Primer 06460.

**APPLICATION**

Always stir well before use. Additives for ease of application or to promote adhesion are not recommended. Do not apply if material, substrate, or ambient temperature is below 50°F or above 110°F. Relative humidity should be below 90%. Apply by brush, roller, or spray. For best brush application results, use a quality synthetic filament brush. For roller application, use a 1/2" to 3/4" nap cover. For spray application, thin with clean water, up to one pint per gallon if necessary.

**APPLICATION EQUIPMENT**

- Apply by brush, roller, or spray.
- Manufacturers listed below are a guide. Others may be used. Changes in pressure and tip size may be required to achieve proper application.

**Airless Spray:**

Pump: Graco / Titan  
High Pressure Filter: 60 Mesh  
Fluid Hose: 1/4" x 50'  
Tips: 0.015" - 0.021"  
Minimum pressure to avoid fingering: 2000 psi

**CAUTIONS --- Lead Hazard: WARNING!**

**If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**

**USE ONLY WITH ADEQUATE VENTILATION.** Wear appropriate respiratory protection when sanding or spraying this product. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid contact with eyes and skin.

**First Aid:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CONTAINER LABELING COMPLIES WITH APPLICABLE STATE RIGHT-TO-KNOW ACTS.** For additional safety and health information, please refer to the Safety Data Sheet (SDS).

Rev 07/19

MANUFACTURED BY:

**McCormick Paints**  
THE PAINT THE PROS USE

2355 Lewis Avenue, Rockville, MD 20851  
Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814  
[www.mccormickpaints.com](http://www.mccormickpaints.com)

**PRODUCT DATA SHEET**