



1st Step

**INTERIOR / EXTERIOR ACRYLIC
CLEAR BRUSHING LACQUER
SURFACE CONDITIONER 9101242**

PRODUCT DATA

GENERIC TYPE: Acrylic Solution

DESCRIPTION: 1st Step Interior/Exterior Acrylic Clear Brushing Lacquer Surface Conditioner is a clear stabilizing surface conditioner. This product has excellent adhesion to a variety of substrates. Its quick drying properties make it ideal for bonding up substrates that have areas of older, peeling paint.

Features:

- Excellent Penetration to Substrate
- Alkali Resistance
- Quick Dry
- Excellent Adhesion

RECOMMENDED USES: For use on interior or exterior substrates. This product can be applied over masonry, drywall or previously painted surfaces. This is an excellent choice in renovation projects where previously painted areas could be fragile due to peeling.

COMPATIBLE COATINGS: Any architectural or construction product can be applied over this conditioner. i.e.: latex paint, elastomeric finishes or solvent based systems.

PHYSICAL CHARACTERISTICS

Colors: Clear
Vehicle Type: Acrylic
VOC/VOS: Less than 680 g/L; 5.7 lb/gal
Volume Solids (Avg.): 9.3% ± 2%
Weight Solids (Avg.): 13.5% ± 2%
Viscosity: 15 Secs Ford Cup 4
Drying Time @ 77°F & 50% R.H.: 10 minutes
Theoretical Coverage per Gallon:
 400-600 sq. ft.
To Touch: 20 minutes
Recoat: 2 hours. Allow additional drying time during humid or cooler weather.
Min. Surface/Air Temperature at Application:
 50°F
Max. Surface/Air Temperature at Application:
 110°F
Flash Point: 12°C/54°F
Application: Brush, Roller or Spray
Clean Up: VM&P Naphtha
Packaging: 5 Gallon
Weight per Gallon: 6.5 – 6.7 lb/gal

GREEN WISE®	LEED	SCAQMD	OTC
NO	NO	NO	YES

APPLICATION INSTRUCTIONS

Apply one (1) coat of McCormick 1st Step Acrylic Clear Brushing Lacquer Surface Conditioner 01242. May also be used as a spot primer, as needed.

APPLICATION EQUIPMENT

- Apply by brush, roller, or spray.
- Best results using a low pressure garden type sprayer. Airless spray equipment can be used, maximum 500 psi.

CAUTIONS --- Lead Hazard: WARNING!

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

USE ONLY WITH ADEQUATE VENTILATION. Wear appropriate respiratory protection when sanding or spraying this product. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid contact with eyes and skin.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CONTAINER LABELING COMPLIES WITH APPLICABLE STATE RIGHT-TO-KNOW ACTS. For additional safety and health information, please refer to the Safety Data Sheet (SDS).

Rev Date 10/19

MANUFACTURED BY:

McCormick Paints
THE PAINT THE PROS USE

2355 Lewis Avenue, Rockville, MD 20851
Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814
www.mccormickpaints.com

PRODUCT DATA SHEET